

## Basic Information

<code>exim -bpc</code>	<i>print a count of the messages in the queue</i>
<code>exim -bp</code>	<i>print a listing of the messages in the queue</i>
<code>exim -bp   exiqsumm</code>	<i>print a summary of messages in the queue</i>
<code>exiwhat</code>	<i>print what exim is doing right now</i>
<code>exim -bP</code>	<i>display all of exim's configuration settings</i>
<code>exim -bt &lt;user@domain&gt;</code>	<i>test how exim will route a given address</i>
<code>exim -bh &lt;IP-Address&gt;</code>	<i>run a pretend smtp transaction from the cli</i>

## Searching the queue with exiqgrep

<code>exiqgrep -f &lt;[user]@domain&gt;</code>	<i>search the queue for messages from a specific sender</i>
<code>exiqgrep -r &lt;[user]@domain&gt;</code>	<i>search the queue for messages for a specific recipient</i>
<code>exiqgrep -o &lt;seconds&gt;</code>	<i>print messages older than &lt;seconds&gt;</i>
<code>exiqgrep -y &lt;seconds&gt;</code>	<i>print messages younger than &lt;seconds&gt;</i>
<code>exiqgrep -s '^7..\$'</code>	<i>match the size of messages with a regex (in bytes)</i>

### Modifiers

<code>-z</code>	<i>match only frozen messages</i>	<code>-i</code>	<i>print only the message-ids</i>
<code>-x</code>	<i>match only unfrozen messages</i>	<code>-c</code>	<i>print a count of matching messages</i>

## Managing the queue

<code>exim -q -v</code>	<i>start a queue run (-ql for local deliveries only)</i>
<code>exim -Mrm &lt;message-id&gt;</code>	<i>remove a message from the queue</i>
<code>exim -Mf &lt;message-id&gt;</code>	<i>freeze a message</i>
<code>exim -Mt &lt;message-id&gt;</code>	<i>thaw a message</i>
<code>exim -M &lt;message-id&gt;</code>	<i>deliver a message, no matter what</i>
<code>exim -Mc &lt;message-id&gt;</code>	<i>deliver a message, if retry time reached</i>
<code>exim -Mg &lt;message-id&gt;</code>	<i>cause message to fail and bounce</i>
<code>exim -Mvh &lt;message-id&gt;</code>	<i>view a message's header (-b body, -l logs)</i>
<code>exim -Mar &lt;msg-id&gt; &lt;address&gt;</code>	<i>add a recipient to a message</i>
<code>exim -Mes &lt;msg-id&gt; &lt;address&gt;</code>	<i>edit the sender of a message</i>

## Searching the logs with exigrep

<code>exigrep '&lt;= .* \[IP-Address\] ' &lt;logfile&gt;</code>	<i>search for messages from a specific IP-address</i>
<code>exigrep '=&gt; .* \[IP-Address\] ' &lt;logfile&gt;</code>	<i>search for messages to a specific IP-address</i>
<code>eximstats &lt;logfile&gt;</code>	<i>generate and display stats from a logfile</i>
<code>eximstats -ne -nr -nt &lt;logfile&gt;</code>	<i>as above but less verbose</i>